



BLUE STAR



**MADE TO DELIVER
BEST-IN-CLASS PRESERVATION.**

Hermetic Series
Refrigeration Systems



Blue Star, India's leading refrigeration company, offers a complete range of evaporating and condensing units. These units are designed to deliver superior cooling for food preservation and are equipped to deliver temperatures for various applications.

The balanced selection of the evaporator and condensing units assures delivery of capacity. The matching controllers with refrigeration units support each installation and enable the controlling and monitoring of temperature. Each Blue Star installation comes with a weather-proof power panel that allows for easy, speedy, safe and long-lasting power connection. So when it comes to cold storage, trust in the experts for reliable, efficient and trouble-free refrigeration.





Evaporating Units

Blue Star's evaporators are compact and sleek. The evaporator is housed within the cold storage and occupies minimum space. This allows you to utilise the maximum volume of cold storage.

Features:

	Stainless steel body (SS304) for enhanced durability and strength		Improved air throw for uniform air distribution
	Excellent corrosion resistance		External rotor driven fans have low noise levels and conform to IP45 standards
	Inner grooved copper tubes for superior heat transfer		Removable side panels for easy service and minimum downtime
	4 FPI coil for medium & low temperature units		Defrost heaters within the coil to ensure total defrost



Condensing Units



Blue Star's condensing units are characterised by high-efficiency heat transfer and low power consumption.

Features:

	Energy-efficient scroll and reciprocating compressors		Pre-charged unit with service valves
	Powder coated body makes these units UV and corrosion-resistant		Safety and control devices for better system protection
	Inner grooved copper tubes and slit aluminium fins for superior heat transfer		Weather-proof polyester powder coated canopy
	Filter drier for protection from moisture and other contaminants		Thermally protected and permanently lubricated fan motors
	Smaller footprint for ease of handling and installation		

Controller

Positive Room Temperature Controller:

Features:

- Specifically designed for refrigeration applications
- Controls compressor cut off and temperature
- Fault alarm indication
- Two-compressor controller with separate set points and differentials



Medium & Negative Room Temperature Controller:

Features:

- 4 digit, 1" dot matrix display
- Precise temperature range : - 50.0°C to + 50.0°C and resolution 0.1° C
- Computer connectivity over RS485
- HP/LP, AUX faults for compressor protection
- Defrost heater operation based on compressor run time



Power Panel

Blue Star's Refrigeration Units come with ready-to-use power panels that make electrical connections simple, fast and long-lasting.

Features:

- Embedded switchgear in the Positive Temperature Condensing Unit
- Power Panel with necessary accessories and defrost controls is available for Medium & Low Temperature Units

Technical Specifications

High Temperature Air-Cooled Refrigeration System with R404A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at +4°C Room Temperature									
Description /Model	Units	RUAH 00614KP-I	RUAH 01014KP-I	RUAH 01514KP-I	RUAH 02014KP-I	RUAH 03014CS-I-N	RUAH 04014CS-I-N	RUAH 06024CS-I-N	RUAH 06014CS-I-N	RUAH 08024CS-I-N	RUAH 08014CS-I-N
Nominal Capacity	Btu/hr	6,000	10,000	15,000	20,000	30,000	40,000	60,000	60,000	80,000	80,000
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50	415/3/50
Fan Motor	Watt	85	85	85	85	250	380	815	815	815	815
	Qty	1	2	3	4	2	2	2	2	2	2
Airflow	CFM	800	1600	2400	3200	4580	5230	12000	12000	11700	11700
Air Throw	Feet	12	14	16	16	25	40	45	45	45	45
No. of Circuits	Nos.	1	1	1	1	1	1	2	1	2	1
Overall Dimensions (WxDxH)	mm	864x480x450	1245x480x450	1780x480x450	2210x480x450	1707x646x718	1707x646x718	2142x841x956	2142x841x956	2142x841x956	2142x841x956
Dry Weight	kgs	18	25	35	45	75	85	140	140	150	150

Blue Star Outdoor Unit		Cooling Capacities at +4°C Room Temperature										
Description/ Model	Units	RUAH OP0614	RUAH OP1014	RUAH OP1514	RUAH OS2014	RUAH OS3014	RUAH OS4014	RUAH OS3014	RUAH OS6014	RUAH OS4014	RUAH OS8014	RUAH OS12014
Nominal Capacity	Btu/hr	6,000	10,000	15,000	20,000	30,000	40,000	2 x 30,000 =60,000	60,000	2 x 40,000 =80,000	80,000	120,000
Compressor Type	-	Hermetic Recip	Hermetic Recip	Hermetic Recip	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1	1	1	1 in each chassis	1	1 in each chassis	1	1
No. of such Chassis	Nos.	1	1	1	1	1	1	2 x RUAHOS3014	1	2 x RUAHOS4014	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	910x370x560	910x370x560	910x370x560	1082x464x657	1082x 464 x1261	1082x464 x1261	1082x464 x1261	1532x654 x947	1082x 464 x1261	1532x654 x947	1450x880 x1115
Each Chassis Dry Weight	kgs	51	61	80	110	125	132	125	185	132	190	275
Each Chassis Refrigerant Pre-charged Qty	kgs	1.2	1.6	2	2.5	3.5	4	3.5	8	4	9	12

Note: Specifications are subject to change without prior notice.

Cooling capacity at the rated condition 35 Amb Temp/+4°C Room Temp /10SH.

Units tested up to 50°C ambient as per standard.

Technical Specifications

High Temperature Air-Cooled Refrigeration System with R410A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at +18°C Room Temperature			
Description/Model	Units	RUAH03611-I	RUAH06611-I	RUAH10211-I	RUAH13211-I
Nominal Capacity	Btu/hr	36,000	66,000	1,02,000	1,32,000
Power Supply	V/Ph/Hz	230/1/50	230/1/50	415/3/50	415/3/50
Fan Motor	Watt	85	380	815	815
	Qty	4	2	2	2
Airflow	CFM	3200	5230	12000	11700
Air Throw	Feet	16	40	45	45
No. of Circuits	Nos.	1	1	1	1
Overall Dimensions (WxDxH)	mm	2210x480x450	1707x646x718	2142x841x956	2142x841x956
Dry Weight	kgs	45	85	140	150

Blue Star Outdoor Unit		Cooling Capacities at +18°C Room Temperature			
Description/Model	Units	RUAH0R3611	RUAH0S6611	RUAH0S10211	RUAH0S13211
Nominal Capacity	Btu/hr	36,000	66,000	1,02,000	1,32,000
Compressor Type	-	Hermetic Rotary	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1
No. of such Chassis	Nos.	1	1	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	1071x464x655	1089x484x925	1417x451x925	1514x651x919
Each Chassis Dry Weight	kgs	80	90	150	190
Each Chassis Refrigerant Pre-charged Qty	kgs	2	4	5	6

Note: Specifications are subject to change without prior notice.

Cooling capacity at the rated condition 35 Amb Temp/+18°C Room Temp /10SH.

Units tested up to 50°C ambient as per standard.

Technical Specifications

Medium Temperature Air-Cooled Refrigeration System with R404A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at -5°C Room Temperature			
Description/Model	Units	RUAM01214-I-N	RUAM01514-I-N	RUAM02014-I-N	RUAM03514-I-N
Nominal Capacity	Btu/hr	12,000	15,000	20,000	35,000
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50
Fan Motor	Watt	85	85	85	380
	Qty	2	3	4	2
Airflow	CFM	1600	2400	3200	5500
Air Throw	Feet	14	16	16	40
No. of Circuits	Nos.	1	1	1	1
Overall Dimensions (WxDxH)	mm	1250x480x440	1780x480x440	2210x480x440	1710x645x720
Dry Weight	kgs	37	45	58	89

Blue Star Outdoor Unit		Cooling Capacities at -5°C Room Temperature			
Description/Model	Units	RUAM01214-O	RUAM01514-O	RUAM02014-O	RUAM03514-O
Nominal Capacity	Btu/hr	12,000	15,000	20,000	35,000
Compressor Type	-	Hermetic Recip	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1
No. of such Chassis	Nos.	1	1	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	1100x464x660	1100x464x660	1100x464x1260	1100x464x1260
Each Chassis Dry Weight	kgs	83	86	131	136
Each Chassis Refrigerant Pre-charged Qty	kgs	2.5	2.5	3.5	4

Note: Specifications are subject to change without prior notice.
Cooling capacity at the rated condition 35 Amb Temp/-5°C Room Temp /10SH.
Units tested up to 50°C ambient as per standard.

Technical Specifications

Low Temperature Air-Cooled Refrigeration System with R404A Refrigerant

Blue Star Indoor Unit		Cooling Capacities at –23°C Room Temperature				
Description/Model	Units	RUAL00614-I-N	RUAL00914-I-N	RUAL01214-I-N	RUAL01814-I-N1	RUAL02414-I-N1
Nominal Capacity	Btu/hr	6,000	9,000	12,000	18,000	24000
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Fan Motor	Watt	85	85	85	380	815
	Qty	2	3	4	2	2
Airflow	CFM	1600	2400	3200	5500	11700
Air Throw	Feet	14	16	16	40	45
No. of Circuits	Nos.	1	1	1	1	1
Overall Dimensions (WxDxH)	mm	1245x480x450	1780x480x450	2210x480x450	1707x646x718	2142x841x956
Dry Weight	kgs	37	45	58	89	135

Blue Star Outdoor Unit		Cooling Capacities at –23°C Room Temperature				
Description/Model	Units	RUAL00614S-O-N1	RUAL00914S-O-N1	RUAL01214S-O-N1	RUAL01814S-O-N1	RUAL02414S-O-N1
Nominal Capacity	Btu/hr	6,000	9,000	12,000	18,000	24,000
Compressor Type	–	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1	1
No. of such Chassis	Nos.	1	1	1	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	1222x539x669	1222x539x669	1240x539x962	1240x539x962	1240x539x962
Each Chassis Dry Weight	kgs	105	115	117	135	148
Each Chassis Refrigerant Pre-charged Qty	kgs	2.5	3	4	5	6

Blue Star Outdoor Unit		Cooling Capacities at –23°C Room Temperature	
Description/Model	Units	RUAL00614P-O	RUAL00914P-O
Nominal Capacity	Btu/hr	6,000	9,000
Compressor Type	–	Hermetic Recip	Hermetic Recip
Power Supply	V/Ph/Hz	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1
No. of such Chassis	Nos.	1	1
Each Chassis Overall Dimensions (WxDxH)	mm	1222x539x669	1222x539x669
Each Chassis Dry Weight	kgs	80	93
Each Chassis Refrigerant Pre-charged Qty	kgs	2.5	3

Note: Specifications are subject to change without prior notice.
Cooling capacity at the rated condition 35 Amb Temp/–23°C
Room Temp /10SH Units tested up to 50°C ambient as per standard.

Notes

[illegible]



Scan QR Code -
Blue Star Customer
Care Mobile App.



• SMS "SERVICE" to 57575



Download Blue Star Customer
Care Mobile App from
App Store & Google Play



To know more about Blue Star, visit
www.bluestarindia.com, email us at
coolingsolutions@bluestarindia.com
or SMS "COOL" to 57575



24X7 CUSTOMER CARE
(Toll Free) 1800 209 1177
1860 266 6666

REGIONAL HEADQUARTERS • Chennai: KRM Plaza, No 2, Harrington Road, Chetpet, Chennai – 600 031. Phone: (+91) (44) 4244 4000, Fax: (+91) (44) 2836 2101 • **Kolkata:** Eco Centre Business Tower, 11th Floor, Unit No: 1 & 2, Plot No 4, EM Block, Sector V, Salt Lake, Bidhannagar, Kolkata – 700 091. Phone: (+91) (33) 4081 5400 • **Mumbai:** Blue Star House, 9A, Ghatkopar, Link Road, Sakinaka, Mumbai – 400 072. Phone: (+91) (22) 6668 4000. Fax: (+91) (22) 6668 4004. • **Gurugram:** 6th Floor, Vatika Atrium, Golf Course Road, Sector 53, Gurugram – 122 002 (Haryana). Phone: (+91) (124) 409 4000. Fax: (+91) (124) 409 4004. **SALES AND SERVICE OFFICES • Ahmedabad:** 201 to 205, Unicus Shyamal, Shyamal Cross Rd, Balgayatri Society Part-2, Satellite, Shyamal, Ahmedabad : 380015 Phone: (+91) (79) 4022 4000. • **Bengaluru:** Anjuman Kay Arr Tower, No 28, Ward No 77, Mission Road, Bengaluru – 560 027. Phone: (+91) (80) 4185 4000. Fax: (+91) (80) 4185 4001. • **Bhubaneswar:** 3A, Satya Nagar, 2nd Floor, Bhubaneswar – 751 007. Phone: (+91) (674) 2572403 / 2573670 / 2570024. Fax: (+91) (674) 257 0544. • **Chandigarh:** Sanjeev Tower, 6th Floor, Plot No 55, Industrial Area Phase 1, Chandigarh – 160002. Phone: (+91) (172) 415 5100. • **Chennai:** Blue Star Limited, 620, Anna Salai, Model School Road, Chennai – 600 006. Phone: (+91) (44) 4996 4000. Fax: (+91) (44) 4044 4001. • **Coimbatore:** Krisan Workspaces, Mayflower Valencia, 4th Floor, Nava India Rd, Coimbatore, 641004. Phone: (+91) (0422) 4377125. Fax: (+91) (0422) 4377127. • **Goa:** 210, 2nd Floor, Gera's Imperium I, Patto, Panjim, Goa – 403 001. Phone: (+91) (832) 2438171/2437287. • **Guwahati:** 5th Floor, 503, Roodraksh Mall, GS ROAD, Bhangaghar, Dispur, Guwahati, Kamrup Metropolitan, Assam, 781005 Phone: (+91) (361) 246 8496. • **Hyderabad:** Ashoka Raghupati Chambers, No 1–10–60 to 64, 4th Floor, S P Road, Begumpet, Hyderabad, Telangana 500 016, India. Phone: (+91) (40) 4400 4000. Fax: (+91) (40) 4400 4001. • **Indore:** Office No. 502, Maloo–0126/C, Scheme No 94/C Ring Road, Indore – 452 010. Phone: (+91) (731) 4001211/4001311. • **Jaipur:** 607–B, 6th Floor, Man Upasana Plaza, Sardar Patel Marg, Jaipur – 302 001 Phone: (+91) (141) 431 3000. Fax: (+91) (141) 512 4899. • **Kochi:** Prestige TMS Square, 9th Floor, No. 2, Service Road, Padivattom, Edappally, Kochi, Kerala 682024. Phone: (+91) (484) 449 9000. Fax: (+91) (484) 449 9190. • **Lucknow:** 5th Floor, BBD Viraj Tower, TCG–1A–V3, Vibhuti Khand, Gomti Nagar, Lucknow, Uttar Pradesh, 226010 Phone: (+91) (522) 403 4000 Fax: (+91) (522) 403 4004. • **Ludhiana:** Goshawk Rental Space Solutions Pvt. Ltd., BXX–3369, Sandhu Tower 2, 2nd Floor, Gurdev Nagar, Ferozepur Road, Ludhiana – 141001. Phone: (+91) (161) 506 4000. • **Nagpur:** 219 Bajaj Nagar, 1st Floor, South Ambazari Road, Nagpur – 440 010. Phone: (+91) (712) 662 4000. Fax: (+91) (712) 662 4002. • **New Delhi:** Unit No 201 & 202, Baani Corporate One, Plot No 5, Second Floor, District Centre, Jasola, New Delhi – 110025 Phone: (+91) (11) 4149 4000. • **Patna:** The Hub, 2nd floor, Near Regent Cinema, Gandhi Maidan Road, Patna – 800004. • **Pune:** 201/A, Nityanand Complex, 247/A Bund Garden Road, Pune – 411 001. Phone: (+91) (20) 4104 4000 / 2616 7230. Fax: (+91) (20) 4104 4001 / 2616 1342. • **Raipur:** MM Silver Plaza, Office No. 103, 1st floor, Opp Udyog Bhavan, Ring Road No. 1, Raipur – 492 001. Phone: (+91) (771) 428 09000. **Surat:** WorkspaceCo (The He Ha Studio), 4th Floor, Kalp Business Centre, Opp. Lavanya Mall, Citylight, Surat : 395007 • **Thane:** Blue Star Limited, Blue Star Innovation Centre, Next to Hotel Vihangs Inn, Kapurbavdi, Ghodbunder Road, Thane West – 400 607 Phone: (+91) (22) 3508 4000 Fax: (+91) (22) 3508 4334. • **Thiruvananthapuram:** TC IV/962, Chandrika, Sree Chitra Nagar, Pipe line Road, Kowdiar, Thiruvananthapuram – 695 003. Phone: (+91) (471) 243 5025. Fax: (+91) (471) 243 4065. • **Vadodara:** INCUSPAZE Office Spaces, 3rd Floor Alembic 1965, Alembic City, Gorwa–Alembic Road, Vadodara – 390003 Phone: (+91) (265) 661 4000/265 233 2021/22 Fax: (+91) (265) 233 7516. • **Vijayawada:** No 40–1–62, Nagas Hafeez Plaza, Opposite to grand modern supermarket, Near BENZ Circle, MG. Road, Vijayawada – 520 010. Phone: (+91) (866) 248 4004. Fax: (+91) (866) 248 4003. • **Visakhapatnam:** Qubexpro Business Centre, V Mall, Lifestyle Building, 4th Floor, Facor Layout, Waltair Uplands, Visakhapatnam – 530003. Phone: (+91) (0891) 6686705.



Blue Star products comply with RoHS regulations as per E-Waste (Management & Handling) Rules, 2016. For disposal of E-Waste, kindly visit our website www.bluestarindia.com or call our customer care 1800 209 1177 (Toll Free) or 1860 266 6666.