

Reach-in Chillers and Freezers



WITH CASTOR WHEELS
FOR EASY MOVEMENT

Easy storage meets accurate temperature control.

Blue Star's range of Reach-in Chillers and Freezers is specially designed for commercial kitchen needs. With upright cabinets that ensure convenient storage and retrieval, and an electronic panel that ensures accurate temperature control, this is the most reliable way of preserving food. Overall, these Chillers and Freezers have a robust design that helps in keeping food fresh for a longer period. Just what you'd expect from the Experts in cooling.

Features



Rounded corners



GN pan compatible



Eco-friendly refrigerant



Adjustable tray slides



Removable gasket for easy clean



Food grade stainless steel unit



Auto defrost



Uniform cooling by forced air circulation



Tropicalised for high ambient temperatures



Castor Wheels



Draw type fan for 360° air circulation



Self-closing doors

Technical Specifications - Reach-in Chillers

Description	RC2D700GP	RC4D1450GP	RC2D700GC	RC4D1450GC	RC2D550N*	RC4D1100N*
Internal Capacity (Ltrs)	650	1350	650	1350	600	1200
Temperature Range (°C)	0° ~ +12	0° ~ +12	0° ~ +12	0° ~ +12	0° ~ +10	0° ~ +10
No. of Door (Nos.)	2	4	2	4	2	4
Cabinet and Doors (Int/Ext)	SS-304/201	SS-304/201	SS-201/201	SS-201/201	SS201/SS201	SS201/SS201
Shelves Qty (Nos.)	2	4	2	4	3	6
Light	Yes	Yes	No	No	No	No
Refrigerant Gas (Type/Charge in grams)	R290/90g	R290/120g	R290/90g	R290/120g	R290/100g	R290/150g
Voltage Supply & Frequency (V - Hz)	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz
Power (Watts)	250	600	250	600	300	490
Current (Amps)	1.3	3.3	1.3	3.3	3.2	5.5
Defrost	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Temperature Display Led	Yes	Yes	Yes	Yes	Yes	Yes
External Dimension(WxDxH) mm	700x880x2043	1400x880x2043	700x880x2043	1400x880x2043	700x765x1997	1200x760x1997
Net Weight (Kg)	112	190	112	190	85	90
Gross Weight (Kg)	122	204	122	204	120	130
Castor Wheels	Yes	Yes	Yes	Yes	Yes	Yes

Technical Specifications - Reach-in Freezers

Description	RF2D700GP	RF4D1450GP	RF2D700GC	RF4D1450GC	RF2D550N*	RF4D1100N*
Internal Capacity (Ltrs)	650	1350	650	1350	600	1200
Temperature Range (°C)	-20° ~ -7	-20° ~ -7	-20° ~ -7	-20° ~ -7	-18° ~ -10	-18° ~ -10
No. of Door (Nos.)	2	4	2	4	2	4
Cabinet and Doors (Int/Ext)	SS-304/201	SS-304/201	SS-201/201	SS-201/201	SS201/SS201	SS201/SS201
Shelves Qty (Nos.)	2	4	2	4	3	6
Light	Yes	Yes	No	No	No	No
Refrigerant Gas (Type/Charge in grams)	R290/115g	R290/120g x 2	R290/115g	R290/120g x 2	R290/110g	R290/150g
Voltage Supply & Frequency (V - Hz)	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz
Power (Watts)	522	950	522	950	400	608
Current (Amps)	2.6	4.9	2.6	4.9	4.2	8.9
Defrost	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Temperature Display Led	Yes	Yes	Yes	Yes	Yes	Yes
External Dimension (WxDxH) mm	700x880x2043	1400x880x2043	700x880x2043	1400x880x2043	700x765x1997	1200x760x1997
Net Weight (Kg)	119	200	119	200	85	90
Gross Weight (Kg)	129	214	129	214	120	130
Castor Wheels	Yes	Yes	Yes	Yes	Yes	Yes

*Non - GN Pan Compatible



For more information, please contact **BLUE STAR LIMITED** • AHMEDABAD: Tel:(079) 40224000 • BENGALURU : Tel: (080) 41854000 • BHUBANESWAR: Tel: (0674) 2572403/2573670 • CHANDIGARH: Tel: (0172) 4155100 • CHENNAI: Tel: (044) 42444000 • GHAZIABAD: Tel: (0120) 2821400 • GOA: Tel: (0832) 2438171 / 2437287 • GUWAHATI: Tel: (0361) 2468496 • GURUGRAM: Tel: (0124) 4094000 • INDORE: Tel: (0731) 4001211 / 4001311 • JAIPUR: Tel: (0141) 3313000 • KOCHI: Tel: (0484) 4499000 • KOLKATA: Tel: (033) 40815400 • LUDHIANA: Tel: (0161) 5001404 • LUCKNOW: Tel: (0522) 4034000 • MUMBAI: Tel: (022) 66684000 • NAGPUR: Tel: (0712) 6624000 • PUNE: Tel: (020) 41044000/26167230 • RAIPUR: Tel: (0771) 4280900 • SECUNDERABAD: Tel: (040) 44004100 • THIRUVANANTHAPURAM: Tel: (0471) 2435025 • VADODARA: Tel: (0265) 6614000/2652332021/22 • VIJAYAWADA: Tel: (0866) 2484004 • VISAKHAPATNAM: Tel: (0891) 6686705
 • email: coolingsolutions@bluestarindia.com • visit us at: www.bluestarindia.com